

<b>Declaration of Performance / DoP</b> Acc. Annex III of the Regulation (EU) Nr. 305/2011 Construction Products Regulation	
<b>FloorBridge Connect 20</b>	
1. Unique identification code of the product-type:	198/V.01
2. Type-, batch- or serial number or a different label for the identification of the building product acc. to article 11 par. 4:	see packaging of the product
3. Intended use:	DIN EN 1504-3:2006-3 Concrete replacement product for structural and non-structural repairs by hand (3.1)
4. Manufacturer:	FloorBridge International Gewerbepark 21 4101 Feldkirchen an der Donau
5. Where appropriate, name and contact address of the authorized representative, mandated with the tasks acc. article 12 par. 2	not relevant
6. System (s) for assessment and verification of constancy of performance of the building product	System 2+ System 3
7. Harmonized standard: Notified body:	EN 1504-3:2006-3 ZA.1a Kiwa GmbH – 0770 MPA Berlin - Brandenburg
8. European technical assessment:	Not relevant



9. Declared performance (s):

EN 1504-3:2006 ZA.1a		
Compressive strength	Class R4 ( $\geq 45$ MPa)	EN 1504-3:2006
Chloride ion content	NPD	
Adhesive	Class R4 ( $\geq 2$ MPa)	
Obstructed shrinking/swelling	NPD	
Karbonatisierungswiderstand	NPD	
Carbonation resistance	NPD	
Thermal shock compatibility	NPD	
Thermal expansion coefficient	NPD	
Capillary water absorption	NPD	
Fire behavior	NPD	
Dangerous substances	NPD	
Grip strength	Class III: $> 55$	
Bending tensile strength	14,5 N/mm <sup>2</sup>	

10. The performance of the product identified in numbers 1 and 2 is in conformity with the set of declared performances in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in number 4.

Signed for and on behalf of the manufacturer by:

Feldkirchen, 13.08.2023

place and date of issue

ppa Ing. Lisa Enzenberger  
product manager/technical manager





0770

FloorBridge International GmbH, Gewerbepark 21, 4101 Feldkirchen an der Donau

2024

198/V.01

EN 1504-3:2006-03

Concrete replacement product for structural and non-structural repairs by hand (3.1)  
EN 1504-3:2006 ZA.1a

Compressive strength	Classs R4 ( $\geq 45$ MPa)
Chloride ion content	NPD
Ahdesive	Class R4 ( $\geq 2$ MPa)
Obstructed shrinking/swelling	NPD
Karbonatisierungswiderstand	NPD
Carbonation resistance	NPD
Thermal shock compatibility	NPD
Thermal expansion coefficient	NPD
Capillary water absorption	NPD
Fire behavior	NPD
Dangerous substances	NPD
Grip strength	Class III: $> 55$
Bending tensile strength	14,5 N/mm <sup>2</sup>

